

| | | | | | | | | | | | | | | | | | | | | | |
|--|------------------------|------------------------|------------------------|------------------------|--------|--------------------------------|--------|--------------------------------|--------|--------------------------------|--------|--------------------------------|--------|--------------------------------|--------|--------|--------|--------|--------|---|---|
| Minimum theoretical power required at the gearbox (TR) | 31 | 35 | 45 | 50 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| Maximum power authorized at the gearbox (WR) | 37 | 37 | 37 | 37 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| Maximum power authorized at the gearbox (TR) | 51 | 51 | 51 | 51 | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| Minimum power requirements for FTD (kW) | - | - | - | - | 26 | 26 | 33 | 33 | 36 | 36 | 38 | 38 | 40 | 40 | 33 | 49 | 7 | 10 | 13 | - | - |
| Minimum power requirements for FTD (kg) | - | - | - | - | 35 | 35 | 45 | 45 | 49 | 49 | 52 | 52 | 54 | 54 | 45 | 67 | 11 | 14 | 18 | - | - |
| Maximum authorized transfer power (TR) | - | - | - | - | 47 | 35 | 50 | 44 | 50 | 44 | 50 | 44 | 50 | 44 | 52 | 52 | 13 | 13 | 14 | - | - |
| Maximum authorized transfer power (kg) | - | - | - | - | 64 | 48 | 80 | 60 | 80 | 60 | 80 | 60 | 80 | 60 | 125 | 125 | 18 | 18 | 19 | - | - |
| Wear control | Roller with fixed ends | Roller with fixed ends | Roller with fixed ends | Roller with fixed ends | Roller | Roller or semi-pressing wheels | Roller | Roller or semi-pressing wheels | Roller | Roller or semi-pressing wheels | Roller | Roller or semi-pressing wheels | Roller | Roller or semi-pressing wheels | Roller | Roller | roller | Roller | Roller | - | - |