

ΦΡΕΖΕΣ
Power tillers

ΤΥΠΟΣ	EL 22-120	EL 22-150	EL 23-120	EL 23-150	EL 43-105	EL 43-130	EL 43-150	EL 43-190	EL 53-100	EL 53-130	EL 53-155	EL 53-190	EL 62-120	EL 62-130	EL 62-155	EL 62-165	EL 62-180	EL 62-210	EL 82-130	EL 82-155	EL 82-180	ΤΥΠΟΣ	
Working width (m)	1.26	1.47	1.26	1.47	1.07	1.27	1.48	1.89	1	1.3	1.55	1.88	1.2	1.3	1.55	1.65	1.8	2.1	1.3	1.55	1.8	Working width (m)	
Rotor diameter (mm)	390	390	390	390	390	390	390	390	430	430	430	430	450	450	450	450	450	450	525	525	525	Rotor diameter (mm)	
Minimum power requirement for PTO (kW)	7	9	7	9	10	12	13	15	13	18	21	24	17	19	22	24	26	31	24	29	33	Minimum power requirement for PTO (kW)	
Minimum power requirement for PTO (hp)	10	12	10	12	14	16	18	20	18	24	28	32	23	25	30	33	35	42	33	39	45	Minimum power requirement for PTO (hp)	
Speed of rotor/s at 540 min ⁻¹ (min ⁻¹)	241	241	241	241	211	211	211	211	244	244	244	244	-	224	224	224	224	224	212	212	212	Speed of rotor/s at 540 min ⁻¹ (min ⁻¹)	
Maximum authorised tractor power (hp)	25	25	25	25	40	40	40	40	50	50	50	50	65	65	65	65	65	65	85	85	85	Maximum authorised tractor power (hp)	
Maximum authorised tractor power (kW)	18.4	18.4	18.4	18.4	29	29	29	29	37	37	37	37	48	48	48	48	48	48	63	63	63	Maximum authorised tractor power (kW)	
Lateral drive mechanism	Chain	Chain	Chain	Chain	Chain	Chain	Chain	Chain	Chain	Chain	Chain	Chain	Chain	Gearwheels	Gearwheels	Gearwheels	Gearwheels	Gearwheels	Gearwheels	Gearwheels	Gearwheels	Gearwheels	Lateral drive mechanism
Type of tools	C-blades	C-blades	C-blades	C-blades	C-blades	C-blades	C-blades	C-blades	C-blades	C-blades	C-blades	C-blades	C-blades	C-blades or L-blades	C-blades or L-blades	C-blades or L-blades	C-blades or L-blades	C-blades or L-blades	C-blades or L-blades	C-blades or L-blades	C-blades or L-blades	C-blades or L-blades	Type of tools
Working depth (min.) (cm)	5	5	5.1	5.1	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	Working depth (min.) (cm)	
Working depth (max.) (cm)	12	12	12.7	12.7	15	15	15	15	15	15	15	15	18	18	18	18	18	18	23	23	23	Working depth (max.) (cm)	
Control of working depth	With skids as standard	With skids as standard	With skids as standard	With skids as standard	With skids as standard + wheels as option	With skids as standard + wheels as option	With skids as standard + wheels as option	With skids or wheels	With skids as standard + wheels as option	With skids as standard + wheels as option	With skids as standard + wheels as option	With skids as standard + wheels as option	With skids or wheels	C-blades or L-blades	Choice of skids or wheels	Choice of skids or wheels	Choice of skids or wheels	Choice of skids or wheels	Choice of skids or wheels	Choice of skids or wheels	Choice of skids or wheels	Choice of skids or wheels	Control of working depth
Weight with skids/wheels (kg)	-	-	-	-	220	235	255	280	250	275	295	295	282	295	330	360	365	420	395/395	430/430	465/465	Weight with skids/wheels (kg)	
Weight approx. (kg)	153	167	144	158	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	Weight approx. (kg)	
Weight in lbs	-	-	317	348	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	Weight in lbs	
Working width (feet)	-	-	49"	57"	42"	50"	58"	74"	38"	50"	60"	74"	-	-	-	-	-	-	-	-	-	71"	Working width (feet)