

3. ΦΕΡΟΖΒΑΡΝΕΣ

Power harrows

Specifications	HR 304	HR 404	HR 3004	HR 3504	HR 4004 R	HR 4004	HR 4504 R	HR 4504	HR 5004 R	HR 6004 R	HR 6040 R	HR 7040 R	HR 8040 R	HRB 122	HRB 152	HRB 182	HRB 202	HRB 252 D	HRB 302 D	HRB 303	HRB 353	Specifications
Working width (m)	3	4	3	3.5	4	4	4.5	4.5	5	6	5.96	6.96	8.05	1.2	1.5	1.8	2.1	2.5	3	3	3.44	Working width (m)
Gearbox	Duplex or Multiplex	Duplex or Multiplex	Duplex	Duplex	Duplex	Duplex	Duplex	Duplex	Duplex	Duplex	Reinforced central gearbox with oil cooler Duplex side gearboxes	Reinforced central gearbox with oil cooler Duplex side gearboxes	Reinforced central gearbox with oil cooler Duplex side gearboxes	Single speed gearbox	Single speed gearbox	Single speed gearbox	Single speed gearbox	Duplex	Duplex	Duplex	Duplex	Gearbox
Minimum power requirement for PTO (kW)	59	73	59	66	81	73	88	81	96	110	131	161	175	18	22	26	30	37	44	51	59	Minimum power requirement for PTO
Minimum power requirement for PTO (hp)	80	100	80	90	110	100	120	110	130	150	180	220	240	25	30	35	40	50	60	70	80	Minimum power requirement for PTO (hp)
PTO speed (rpm)	1000/750/540	1000/750/540	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	540	540	540	540	540 and 1000	540 and 1000	1000/750/540	1000/750/540	PTO speed (rpm)
Maximum authorised tractor power (hp)	190	190	250	250	250	250	250	250	250	280	460	480	500	80	80	80	80	140	140	160	160	Maximum authorised tractor power (hp)
Maximum authorised tractor power (kW)	140	140	184	184	184	184	184	184	184	206	336	345	365	59	59	59	59	103	103	118	118	Maximum authorised tractor power (kW)
Transmission	With cam type cut-out clutch	With cam type cut-out clutch	With cam type cut-out clutch	With cam type cut-out clutch	With cam type cut-out clutch	With cam type cut-out clutch	With cam type cut-out clutch	With cam type cut-out clutch	With cam type cut-out clutch	With cam type cut-out clutch	Walterscheid P600	Walterscheid P600	Walterscheid P600	With shear bolt cut-out clutch	With shear bolt cut-out clutch	With shear bolt cut-out clutch	With shear bolt cut-out clutch	With adjustable friction slip clutch	With adjustable friction slip clutch	With cam type cut-out clutch	With cam type cut-out clutch	Transmission
Weight with Maxicrumbler roller (kg)	1100 (Duplex) 1140 (Multiplex)	1470 (Duplex) 1510 (Multiplex)	1195	1400	2115	1580	2275	1730	2350	2900	4015	4350	4410	-	-	-	-	-	975	1085	1296	Weight with Maxicrumbler roller (kg)
Weight with packer roller (kg)	-	-	-	-	1820	-	1820	-	1820	-	-	-	-	-	-	-	840	975	-	-	-	Weight with packer roller (kg)
Weight with Packer PK2 roller (kg)	1295 (Duplex) 1335 (Multiplex)	1740 (Duplex) 1780 (Multiplex)	1390	1635	2340	1850	2520	2020	2625	3290	-	-	-	-	-	-	-	-	1170	1280	1525	Weight with Packer PK2 roller (kg)
Weight with Maxipacker roller (kg)	1325 (Duplex) 1365 (Multiplex)	1790 (Duplex) 1830 (Multiplex)	1420	1685	2390	1900	2595	2075	2700	3350	4515	4930	5070	-	-	-	-	-	1200	1310	1575	Weight with Maxipacker roller (kg)
Weight with cage roller (kg)	-	-	-	-	-	-	-	-	-	-	-	-	-	440	500	550	720	835	965	1075	1300	Weight with cage roller (kg)
Approx. weight (kg) - Megapacker roller	-	-	-	-	-	-	-	-	-	-	4600	5030	5195	-	-	-	-	-	-	-	-	Approx. weight (kg) - Megapacker roller
Approx. weight (kg) - Steelliner roller	-	-	-	-	-	-	-	-	-	-	4700	5130	5305	-	-	-	-	-	-	-	-	Approx. weight (kg) - Steelliner roller
Working width (feet)	-	-	9'10"	11'6"	-	13'	-	15'	16'5"	20'	-	-	-	4'	5'	6'	6'8"	8'2"	9'10"	-	-	Working width (feet)
Transport width (m)	-	-	-	-	-	-	-	-	-	-	3	3	3	-	-	-	-	-	-	-	-	Transport width (m)