

6 .ΚΤΗΝΟΤΡΟΦΙΚΑ

Straw Blowers & Feeders with Hydraulic Beater

ΦΟΡΤΙΣΗ - ΣΤΡΩΣΙΜΟ

ΤΥΠΟΣ	ΦΕΡΟΜΕΝΟ		ΤΥΠΟΣ	ΣΥΡΟΜΕΝΟ	
	PRIMOR 2060 H mounted	PRIMOR 2060 H trailed		POLYCROK 3850	
Linkage	mounted	trailed	Semi-mounted		
Number of feed rotors	1	1	3		
Capacity (m ³)					
Overall width (m)	1.76	2.08			
Weight (kg)	1200	1380			
Recommended maximum square bale dimensions (m)	2.70x1.30x1.20	2.70x1.30x1.20			
Recommended maximum round bale dimensions (diameter in m)	1.95	1.95	1.200		
Minimum power requirement for PTO (kW)	51	37	Maize and grass silage (<15cm)		
Minimum power requirement for PTO (hp)	70	51	Maximum number of Dairy Cows which can be fed with one load	24	

Trailed Silage Cutters & Feeders

ΦΟΡΤΙΣΗ - ΚΟΥΡΙΜΟ - ΤΑΞΙΜΑ

ΤΥΠΟΣ	ΦΕΡΟΜΕΝΟ		ΤΥΠΟΣ	ΣΥΡΟΜΕΝΟ	
	PRIMOR 2060 H mounted	PRIMOR 2060 H trailed		POLYCROK 3850	
Linkage	mounted	trailed	Semi-mounted		
Number of feed rotors	1	1	3		
Capacity (m ³)					
Overall width (m)	1.76	2.08			
Weight (kg)	1200	1380			
Recommended maximum square bale dimensions (m)	2.70x1.30x1.20	2.70x1.30x1.20			
Recommended maximum round bale dimensions (diameter in m)	1.95	1.95	1.200		
Minimum power requirement for PTO (kW)	51	37	Maize and grass silage (<15cm)		
Minimum power requirement for PTO (hp)	70	51	Maximum number of Dairy Cows which can be fed with one load	24	

Single Auger Vertical TMR Mixers

ΤΥΠΟΣ	ΣΥΡΟΜΕΝΑ ΜΙΣΗ - ΤΑΞΙΜΑ																		Specifications				
	PROFILE 4.1 DS	PROFILE 6.1 DS	EUROMIX 1870	EUROMIX 1070	EUROMIX 1270	S127	S135	S143	PROFILE 10.1 CL	PROFILE 10.1 DL	PROFILE 11.1 CL	PROFILE 11.1 DL	PROFILE 12.1 CL	PROFILE 12.1 DL	PROFILE 13.1 CL	PROFILE 13.1 DL	PROFILE 14.1 CL	PROFILE 14.1 DL		PROFILE 15.1 CL	PROFILE 15.1 DL	PROFILE 9.1 CL	
Capacity (m ³)	4	6	8	10	12	7.8	9.9	12	10	10	11	11	12	12	13	13	14	14	15	15	9	Capacity (m ³)	
Capacity (cu.R)	-	-	-	-	-	270	350	430	-	-	-	-	-	-	-	-	-	-	-	-	-	Capacity (cu.R)	
Augers	Vertical	Vertical	Vertical	Vertical	Vertical	-	-	-	Vertical	Vertical	Vertical	Vertical	Vertical	Vertical	Vertical	Vertical	Vertical	Vertical	Vertical	Vertical	Vertical	Augers	
Number of augers	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	Number of augers	
Distribution type	Right and left (side delivery)	Right and left (side delivery)	Right and left (side delivery)	Right and left (side delivery)	Right and left (side delivery)	-	-	-	Transverse right and left	Lateral right and left	Transverse right and left	Lateral right and left	Transverse right and left	Lateral right and left	Transverse right and left	Lateral right and left	Transverse right and left	Lateral right and left	Transverse right and left	Lateral right and left	Transverse right and left	Distribution type	
Overall height (m)	2.05	2.33	2.45	2.78	3.03	-	-	-	From 2.50 to 2.66	From 2.50 to 2.66	From 2.61 to 2.77	From 2.61 to 2.77	From 2.74 to 2.90	From 2.74 to 2.90	From 2.86 to 3.02	From 2.86 to 3.02	From 2.99 to 3.15	From 2.99 to 3.15	From 3.12 to 3.28	From 3.12 to 3.28	From 2.37 to 2.54	Overall height (m)	
Overall height - no extensions (cm)	-	-	-	-	-	231	257	287	-	-	-	-	-	-	-	-	-	-	-	-	-	Overall height - no extensions (cm)	
Overall height - no extensions (inch)	-	-	-	-	-	91	101	113	-	-	-	-	-	-	-	-	-	-	-	-	-	Overall height - no extensions (inch)	
Overall width (m)	2.21	2.24	2.35	2.35	2.35	-	-	-	2.8	2.79	2.8	2.79	2.81	2.8	2.82	2.81	2.86	2.82	2.87	2.84	2.8	Overall width (m)	
Overall width - without options (cm)	-	-	-	-	-	254	254	254	-	-	-	-	-	-	-	-	-	-	-	-	-	Overall width - without options (cm)	
Overall width (inch)	-	-	-	-	-	100	100	100	-	-	-	-	-	-	-	-	-	-	-	-	-	Overall width (inch)	
Tread width (cm)	-	-	-	-	-	208	208	208.28	-	-	-	-	-	-	-	-	-	-	-	-	-	Tread width (cm)	
Tread width (in)	-	-	-	-	-	82	82	82	-	-	-	-	-	-	-	-	-	-	-	-	-	Tread width (in)	
Weight (kg)	1840	2060	2970	3040	3160	2313	2586	2803	4420	3940	4450	3970	4510	4020	4550	4070	4860	4120	4920	4190	4290	Weight (kg)	
Weight (lb)	-	-	-	-	-	5100	5700	6180	-	-	-	-	-	-	-	-	-	-	-	-	-	Weight (lb)	
Drive	-	-	-	-	-	Planetary	Planetary	Planetary	-	-	-	-	-	-	-	-	-	-	-	-	-	Drive	
PTO speed (rpm)	-	-	-	-	-	540	540	540	-	-	-	-	-	-	-	-	-	-	-	-	-	PTO speed (rpm)	
Minimum power requirement for PTO (kW)	29	33	44	51	59	37	56	67	48	48	51	51	55	55	59	59	59	59	59	63	63	44	Minimum power requirement for PTO (kW)
Minimum power requirement for PTO (hp)	40	45	60	70	80	50	75	90	65	65	70	70	75	75	80	80	80	80	85	85	85	60	Minimum power requirement for PTO (hp)
Maximum number of Dairy Cows which can be fed with one load	between 20 and 40	between 30 and 45	between 40 and 60	between 50 and 75	between 60 and 90	-	-	-	between 50 and 75	between 50 and 75	between 55 and 85	between 55 and 85	between 60 and 90	between 60 and 90	between 65 and 100	between 65 and 100	between 70 and 105	between 70 and 105	between 75 and 110	between 75 and 110	between 45 and 70	Maximum number of Dairy Cows which can be fed with one load	
Maximum load (kg)	-	-	-	-	-	3062	3969	4876	-	-	-	-	-	-	-	-	-	-	-	-	-	-	Maximum load (kg)
Door opening (HxW cm)	-	-	-	-	-	91x99	91x99	91x99	-	-	-	-	-	-	-	-	-	-	-	-	-	-	Door opening (HxW cm)
Door opening (HxW inch)	-	-	-	-	-	36x39	36x39	36x39	-	-	-	-	-	-	-	-	-	-	-	-	-	-	Door opening (HxW inch)
Auger Diameters (cm)	-	-	-	-	-	218	218	218	-	-	-	-	-	-	-	-	-	-	-	-	-	-	Auger Diameters (cm)
Auger Diameters (inch)	-	-	-	-	-	86	86	86	-	-	-	-	-	-	-	-	-	-	-	-	-	-	Auger Diameters (inch)