

ΣΠΑΡΤΙΚΕΣ

ΠΝΕΥΜΑΤΙΚΕΣ ΣΠΑΡΤΙΚΕΣ

Mounted pneumatic precision seed drill single bar

Specifications	<u>MAXIMA 2 M (Single bar 250 - 440)</u>	<u>MAXIMA 2 M (Single bar 500 - 900)</u>	<u>PLANTER 3 M (Single Bar) 250 - 440</u>	<u>PLANTER 3 M (Single Bar) 500 - 900</u>	<u>PLANTER 3 M (Single Bar)</u>
Working width (m)	-	-	between 2,5 and 4,4	between 5 and 9	between 2,5 and 9
Frame type	Single bar	Single bar	Single bar	Single bar	Single bar
Frame width in working position (m)	2.50 to 4.40	5.00 to 9.00	-	-	-
Frame width in transport position (m)	2.50 to 4.40	5.00 to 9.00	-	-	-
Distribution type	-	Pneumatic	-	-	-
Number of seeding units	4 to 11	From 8 to 18	-	-	-
Row spacing (cm)	37.5 to 80	From 45 to 80 (depending on number of rows and seeding unit equipment)	as from 25	as from 25	as from 25
Hopper capacity (l)	52	52	47	47	47
Fertilisation	2x190l or 2x280l or 1x950l (depending on model)	With a 1350 l hopper or with a front hopper (depending on model)	Polyethylene hoppers with row by row grooved distribution Capacities of 2x190. 2x280. 1x950 l. or 1x1350l.	Polyethylene hoppers with row by row grooved distribution Capacities of 2x190. 2x280. 1x950 l. or 1x1350l.	Polyethylene hoppers with row by row grooved distribution Capacities of 2x190. 2x280. 1x950 l. or 1x1350l.
Microgranulator	Insecticide, slug pellets and weed killer depending on model)	Insecticide, slug pellets and weed killer depending on model)	In the seed line (insecticide type) from 60 to 180 L In the seed line (anti-slug type) from 60 to 180 L	In the seed line (insecticide type) from 60 to 180 L In the seed line (anti-slug type) from 60 to 180 L	In the seed line (insecticide type) from 60 to 180 L In the seed line (anti-slug type) from 60 to 180 L
Gearbox	1 (20 ratios)	1 or 2 (20 ratios)	-	-	-
Number of wheels	2	4 or 6 (depending on model)	-	-	-
Average weight of seeding unit (kg)	120/150	120/150	-	-	-
Markers	With DA hydraulic control	With DA hydraulic control	-	-	-
Linkage	Semi automatic	Semi-automatic	-	-	-
Disengagement of the seeding units	Simple knob as standard	Simple knob as standard	-	-	-

ΜΗΧΑΝΙΚΕΣ ΣΠΑΡΤΙΚΕΣ

Mounted seed drills mechanical

ΤΥΠΟΣ	<u>MGD 5200-15 3PT</u>	<u>MGD 5200-15 3PT</u>	<u>MGD 5200-20 3PT</u>	<u>MGD 5200-20 3PT</u>	<u>PREMIA 250</u>	<u>PREMIA 3000</u>	<u>PREMIA 300</u>	<u>PREMIA 3500</u>	<u>PREMIA 4000</u>
Row spacing (cm)	25. 19. or 15	25. 19. or 15	25. 19. or 15	25. 19. or 15	12.5	15 or 12.5	15 or 12.5	14.3 or 12.5	14.3 or 12.5

Working width (m)	4.5	4.5	6	6	2.5	3	3	3.43 or 3.38	4
Working speed (km/h)	08-Dec	08-Dec	08-Dec	08-Dec	-	-	-	-	-
Number of coulters	-	-	-	-	20	20 - 24	20 - 24	24-27	28 - 32
Number of rows	18. 24. or 30	18. 24. or 30	24. 32. or 40	24. 32. or 40	20	-	-	-	-
Row spacing (inches/cm)	10". 7.5". or 6"	10". 7.5". or 6"	10". 7.5". or 6"	10". 7.5". or 6"	-	-	-	-	-
Number of openers	18. 24. or 30	18. 24. or 30	24. 32. or 40	24. 32. or 40	-	-	-	-	-
Opener diameter (cm)	34.3	34.3	34.3	34.3	-	-	-	-	-
Opener diameter (in)	13.5"	13.5"	13.5"	13.5"	-	-	-	-	-
Hopper capacity (l)	-	-	-	-	380	780 (1080 with extension)	480 (710 with extension)	900 (1250 with extension)	1080 (1480 with extension)
Filling height approx. (m)	-	-	-	-	1.25	1.42	1.25	1.42	1.42
Maximum hopper capacity (l)	1691	1691	2255	2255	-	-	-	-	-
Max Hopper Capacity (cu.ft.)	59.7	59.7	79.6	79.6	-	-	-	-	-
Application (kg/ha)	-	-	-	-	0.8	0.8	0.8	0.8	0.8
Seed/fertilizer capacity	60%/40%	60%/40%	60%/40%	60%/40%	-	-	-	-	-
Frame type	3 PT Rigid	3 PT Rigid	3 PT Rigid	3 PT Rigid	-	-	-	-	-
Coulter bar	-	-	-	-	Suffolk or single disc coulters	Suffolk or single disc coulters	Suffolk or single disc coulters	Suffolk or single disc coulters	Suffolk or single disc coulters
Number of wheels	2	2	2	2	-	-	-	-	-
Maximum authorised tractor power (hp)	100	100	120	120	-	-	-	-	-
Maximum authorised tractor power (kW)	75	75	90	90	-	-	-	-	-
Transport width (m)	4.9	4.9	6.5	6.5	-	-	-	-	-
Transport width (feet)	15' 11"	15' 11"	21' 4"	21' 4"	-	-	-	-	-
Transport Height (m)	2.4	2.4	2.4	2.4	-	-	-	-	-
Transport Height (feet)	8'	8'	8'	8'	-	-	-	-	-

Number of sections	1	1	1	1	-	-	-	-	-
Weight in kg.	between 1431 and 1826	between 1431 and 1826	between 1836 and 2363	between 1836 and 2363	-	-	-	-	-
Weight in lbs	between 3154 and 4026	between 3154 and 4026	between 4047 and 5209	between 4047 and 5209	-	-	-	-	-
Covering harrow	-	-	-	-	Standard. with tines	Standard. with tines	Standard. with tines	Standard. with tines	Standard. with tines
Working speed (km/h)	between 8 and 12	between 8 and 12	between 8 and 12	between 8 and 12	-	-	-	-	-
Working speed (m.p.h.)	between 5 and 7	between 5 and 7	between 5 and 7	between 5 and 7	-	-	-	-	-
Number of discs	-	-	-	-	20	20 - 24	20 - 24	24-27	